



WED-80C ET2

High spin washers



EASY TOUCH 2

7" touch screen, user-friendly and fully programmable
Connection USB. Free software online for programming, telemetry, data analysis...
Videos display (ads, instructions...)
37 available languages
8 dosing signals as standard



G FACTOR

High G factor: reduced residual moisture, reduced drying time, energy savings



EFFICIENCY

Optimized consumption: automatic or manual adjustment of water levels and detergents according to the load
Water Saving system: 3 configurable levels of savings
Ready for water recovery tanks AQUABAC



VERSATILITY

ELECTRIC <> HOT WATER
MAKE TO ORDER: possibility to customize
WET CLEANING as standard



CONNECTIVITY

Communication Danube Online - IoT as standard
Remote technical service
Management of laundry
Multi-payment system



ERGONOMICS

Big aluminium door
Easy door lock system



MAINTENANCE

Hinged panel: easy access to parts
Technical menu: statistics, errors...



OTHERS

Free standing: no anchoring to the floor
Stainless steel vat and drum, skinplate outer casing
3 water inlets
Detergents box with compartments
Imbalance controlled by frequency inverter
CE standards and KIWA for REG4 standards



OPTIONS

- Dosing pumps kit DQ-2
- Additional dosing pump DB-1
- RT Ready for AQUABAC XL conn. 1" for washers WEN/WED-60C/80C
- DD Double drain kit WED-60C-80C
- Kit WATERMARK Australia
- NC Normally closed valve WED-60C/80C
- TL2 Double tilting kit WED-60C/80C
- TL1 Frontal tilting kit WED-60C/80C
- Water hose kit WED/WEN-60C/80C (one per water intake)
- WS weighing system WED-60C to 120C (XD card to be ordered separately)
- XD 6 extra dosing signals card WED-60C-120C
- RD reverse door opening
- TR Protected board ET2 for WED-11-45C (standard on 60 to 120 kg models)
- Steam kit WED-60C/80C (to transform E or HW models to steam)
- DH Dual heating kit WED-60C/80C
- SSC Stainless steel outer casing AISI-304 WED-80C
- 440V 3~ (No N) 50/60 Hz 80C
- 230V 3~ 50/60Hz 80C
- 230V III 50/60 - 80 kg
- IoT licence - Danube Online

TECHNICAL DATA	UNIT.	WED-80C ET2	
DRUM			
Load capacity 1:9 / 1:10	Kg	85/77	
Volume	l	770	
	gal	203,4	
Diameter	mm	1048	
	inch	41,2	
Depth	mm	892	
	inch	35,1	
GENERAL DATA			
Washing speed / Spin speed	r.p.m.	38 / 875	
G factor	-	450	
Maximum transmitted force	KN	23 ±4,8	
Dynamic force frequency	Hz	12,66	
Sound level	dB	< 70	
Self-service version	-	NO	
Double drain	-	OPT.	
Weighing system / Tilting system	-	OPT.	
SLUICE option	-	NO	
DOOR			
Door centre height / Door base height	mm	1170 / 810	
	inch	46 / 31,88	
Diameter	mm	560	
	inch	22	
POWER			
Motor	kW	15	
Electric heating (electric model)	kW	48/36	
Maximum electric power	kW	51/39	
Max. power steam & hot water model	kW	15	
CONNECTIONS		E	HW/S
Voltage 110V - 1 + N + E	Nº x mm2 / A	-	-
	Nº x AWG / A	-	-
Voltage 230V - 1 + N + E	Nº x mm2 / A	-	-
	Nº x AWG / A	-	-
Voltage 230V - 3 + E	Nº x mm2 / A	4x25 / 100A	4X6 / 40A
	Nº x AWG / A	4x3 / 120A	4x9 / 50A
Voltage 400V - 3 + N + E	Nº x mm2 / A	5x25 / 80A	5x10 / 50A
	Nº x AWG / A	5x3 / 90A	5x7 / 30A
Steam inlet (steam model)	inch	3/4"	
Max. steam consumption (steam model)	Kg/h	25	
Water inlet	inch	1"	
Water pressure	Kgs/cm2	2-4	
Max. water consumption*	Lit/h	781	
	GPH	206,3	
Drain	inch	3"	
Drain capacity	Lit/min	200	
	GPM	52,8	
DIMENSIONS / PACKING DIMENSIONS			
Net width / Gross width	mm	1.420/1.600	
	inch	55,9 / 62,99	
Net depth / Gross depth	mm	1.645/1.805	
	inch	64,7 / 71	
Net height / Gross height	mm	1.890/1.930	
	inch	74,4 / 75,98	
Net weight / Gross weight	kg	1.800/2.000	
	lb	3968,3 / 4409,2	



Packing volume	m3	5,6
	ft3	197,7

*Programme no.20, 75% load
 **Programme no.2, 100% load

